

# DH-EAC10-P

Wireless Access Controller EAC10-P with 10-Port PoE



- Wireless Access Controller.
- Multi WAN-port mode.
- EAP Series AP Management.
- Flexible Forwarding Modes.
- Smart Roaming Features.
- Various kinds of network authentication methods.



## Series Overview

EAC Series Wireless Access Controller (AC) is well designed and positioned for SMB network. It features gateway and AC function integration, reducing the number of devices and TCO in network. It comes with the standard granular user control management, comprehensive RF resource management, 24/7 wireless security control, fast roaming, strong QoS. When paired with EAP Series Access Point (AP), it serves as an ideal access control solution for WLAN access of SMB network.

## Functions

### All-in-one Gateway

Performs routing and switching, and supports AP management and PoE power supplies, making it convenient for networking and testing.

### Smart Wireless Networking

Works with AP, and performs distributed networking, and unified operation and maintenance. The device provides wide Wi-Fi coverage, seamless roaming and is plug and play.

### Strong Control of Network Traffic Flow

Limits the uplink and downlink bandwidth, and the speed of users, meeting the needs of network management.

## Technical Specification

### Hardware

PoE Power Supply	Yes
PoE Power	Full load: 64 W
Ethernet Port	10
Ethernet Port Speed	10/100/1000 Mbps
Description of Function Slots	Port 1-8: 8 × 10/100/1000Base-T RJ-45/PoE Out Port 9-10: 2 × 10/100/1000Base-T RJ-45
LAN Port	9 × 1000 Mbps (1 LAN port can be switched to WAN port)
WAN Port	1 × 1000 Mbps
Reset Button	1
Power Supply	External power supply: 54 VDC, 1.33 A
Power Consumption	Idling: 8 W Full load: 72 W
Protection	IP20

### Function

802.11 LAN Protocols	802.11n;802.11b;802.11ax;802.11a;802.11g;802.11ac
CAPWAP	Layer 2 network topology between an AP and AC Enable an AP to automatically discover an accessible AC Enable an AP to automatically download configurations from an AC
Roaming	Intra-AC roaming
Forwarding	Local forwarding Centralized forwarding
Wireless QoS	AP-based bandwidth control WLAN-based bandwidth control User-based static and smart speed control Fair balancing
User Isolation	WLAN-based user isolation
User Management	Access control based on SSID user number

<b>RF Management</b>	Country code configuration Manual configuration of transmitting power Manual configuration of working channel Automatically allocation of working channel Scheduled reallocation of wireless channel
<b>PoE Protocol</b>	IEEE 802.3af
<b>WAN Port Function</b>	Dynamic IP Static IP PPPoE IP/Mask configuration MTU configuration TCP MSS configuration Network bandwidth configuration Gateway address assignment NQA configuration to probe address
<b>Multi-WAN Load Balancing</b>	Distributing network traffic equally Ratio load balancing Multi-link for load balancing
<b>Link Detection</b>	Enable and disable link detection ICMP probe TCP probe
<b>IP Routing</b>	Static routing Policy-based routing
<b>VPN</b>	L2TP VPN PPTP VPN
<b>DHCP Function</b>	DHCP Server DHCP Client
<b>Security</b>	Portal Authentication PPPoE Authentication IP/MAC Authentication IP/MAC Binding Intranet Anomaly Detection Intranet Attack Protection WAN Ping Forbid Virtual AP Multiple SSIDs SSID Hiding WPA/WPA2 WPA3 WEP(WEP/WEP128) TKIP
<b>QoS/ACL</b>	Traffic supervision Congestion management Congestion avoidance Traffic shaping IP-based speed limit Traffic classification
<b>Equipment Management</b>	Web Management TFTP FTP NTP System Log Ping

## Performance

<b>Default Number of Manageable APs</b>	10
<b>Maximum Number of Manageable APs</b>	10
<b>Maximum Number of Configurable APs</b>	10
<b>Users Capacity</b>	1K
<b>Firewall</b>	500 Mbps
<b>Encryption</b>	500 Mbps
<b>Forwarding Capability</b>	500 Mbps
<b>CPU Frequency</b>	880 MHz

<b>Processor</b>	Dual core
<b>MTBF</b>	40,000 hours
<b>Memory</b>	256 MB
<b>Flash</b>	16 MB
<b>Packet Buffer Size</b>	2 MB
<b>MAC Address List</b>	1024
<b>Entries of MAC Address Filtering Table</b>	32
<b>IPv4 Forwarding</b>	1 Gbps
<b>Static Routes</b>	200
<b>Max. Number of Static DNS Records</b>	256
<b>Max. Number of DDNS Records</b>	4
<b>Static ARP</b>	1K
<b>Dynamic ARP</b>	2K
<b>ACL</b>	1K
<b>L2TP Users</b>	128
<b>Max. Number of Tunnels</b>	128
<b>Max. Number of Sessions</b>	128
<b>Max. Number of Concurrent Connections</b>	200K
<b>New Connections</b>	6K
<b>Max. Number of Virtual Servers</b>	100
<b>Max. Number of Port Triggering</b>	20
<b>Aging Time of Port Triggering</b>	10 min
<b>Number of NAT</b>	30

## General

<b>Operating Temperature</b>	-20 °C to +55 °C (-4 °F to +131 °F)
<b>Operating Humidity</b>	5%–95% (RH), non-condensing
<b>Storage Temperature</b>	-40 °C to +70 °C (-40 °F to 158 °F)
<b>Storage Humidity</b>	5%–95% (RH), non-condensing
<b>Statics Protection</b>	Air discharge: 8 kV; Contact discharge: 6 kV
<b>Lighting Protection</b>	Common mode: 2 kV
<b>Net Weight</b>	0.46 kg (1.01 lb)
<b>Gross Weight</b>	0.98 kg (2.16 lb)
<b>Product Dimensions</b>	190 mm × 97.5 mm × 29.5 mm (7.48" × 3.84" × 1.16") (L × W × H)
<b>Packaging Dimensions</b>	225 mm × 216mm × 66mm (8.85" × 8.50" × 2.60") (L × W × H)
<b>Installation</b>	Desktop mount
<b>Certifications</b>	CE; FCC

## Dimensions (mm [inch])

