

Eaton 5E2200UI

Catalog Number: 5E2200UI

Eaton 5E Gen2 UPS USB IEC, 2200 VA, 1200 W, Input: C14, Outputs: (6) C13, Tower



General specifications

Product Name	Catalog Number
Eaton 5E Gen2 UPS	5E2200UI
EAN	Product Length/Depth
3553340704376	330 mm
Product Height	Product Width
180 mm	133 mm
Product Weight	Warranty
9.82 kg	2 year
Compliances	Certifications
CB	IEC/EN 62040-1
LVD Directive	IEC/EN 62040-2
EMC Directive	CE
RoHS Directive	EAC
Packaging Directive	UKCA
WEEE Directive	Cm
Batteries Directive	Ukr
	IEC/EN 62040-3

Product specifications

Special features

Automatic Voltage Regulation (AVR)
Saves space with a compact tower design
HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)

Type

UPS

Topology

Line-interactive

Form factor

Tower

Construction type

Free standing model

Color

Black

VA rating

2200 VA

Wattage

1200 W

Rack mounting kit

No

Package contents

(2) IEC-IEC output cables
Quick start
Safety instructions

Surge protection

Yes

Internal bypass

No

Hot swap power

No

Auto shutdown function

Resources

Brochures

[eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf](#)

Certification reports

[eaton-dpq-5egen2-ups-certificate-en-gb.pdf](#)

Manuals and user guides

[eaton-dpq-5egen2-ups-manual-en-gb.pdf](#)

Technical data sheets

[eaton-dpq-5egen2-ups-datasheet-en-gb.pdf](#)

Yes

Primary frequency - max

63 Hz

Primary frequency - min

45 Hz

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input frequency range

45-63 Hz

Receptacle

(6) C13

Number of Outputs C13

6

Voltage

230V

Output nominal voltage

230V

Feed type

1

Voltage type

AC

Runtime graph

[View runtime graph](#)

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Battery rating

12 V / 9 Ah

Battery type

Sealed, lead-acid

Extended battery capability

No

Communication

USB port (HID compliant)

Expansion slots

No

Ethernet interface

No

Includes network card

No

Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

User interface

LEDs

Type of interface

USB

Potential free switch contact

No

Relative humidity

0-90% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Operating temperature - max

40 °C

Operating temperature - min

0 °C

Output apparent power

2200 VA

Input voltage - max

300 V

Input voltage - min

140 V

Output voltage - max

257 V

Output voltage - min

195 V

Secondary frequency - max

60 Hz

Secondary frequency - min

50 Hz

Battery quantity

2

Efficiency

95

Input voltage range

140-300 V

Output frequency

50/60 Hz

Output voltage range

195-257 V

Phase (input)

1

Phase (output)

1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)