





SPECIFICATIONS

Active Display Area (mm) Curvature Flat Panel Type Rapid IPS Panel Resolution Pixel Pitch (H x V) Aspect Ratio Brightness (nits) Contrast Ratio DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) USB ports Audio ports 1 x Readphone out Viewing Angle Angle 1 78° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Flivot) Adjustment (Flivot) Adjustment (Height) Carton Dimension (W x D x H) Frameless Design Pyes PIP / PBP Function N/A Po.2331(H) x 335.664(V) Rapid IPS Rapi	Panel Size	27" (69 cm)
Panel Type Rapid IPS Panel Resolution 2560 x 1440 (WQHD) Pixel Pitch (H x V) 0.2331(H)x0.2331(V) Aspect Ratio 16:9 Brightness (nits) 300 (Typ.) Contrast Ratio 1200:1 DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE AMD FreeSync™ TECHNOLOGY HDR Ready Video ports 1 x DisplayPort (1.4) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.078 (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm <th>Active Display Area (mm)</th> <th>596.736(H) x 335.664(V)</th>	Active Display Area (mm)	596.736(H) x 335.664(V)
Panel Resolution 2560 x 1440 (WQHD) Pixel Pitch (H x V) 0.2331(H)x0.2331(V) Aspect Ratio 16:9 Brightness (nits) 300 (Typ.) Contrast Ratio 1200:1 DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE TECHNOLOGY AMD FreeSync™ HDR Ready 1 x DisplayPort (1.4) Video ports 1 x DisplayPort (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Pivot) -90° ~ 90° Adjustment (Height)	Curvature	Flat
Pixel Pitch (H x V) 0.2331(H)x0.2331(V) Aspect Ratio 16:9 Brightness (nits) 300 (Typ.) Contrast Ratio 1200:1 DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE TECHNOLOGY AMD FreeSync™ HDR Ready 1 x DisplayPort (1.4) Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) 2 x HDMI™ (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Pivot) -90° ~ 90° Adjustment (Pivot) -90° ~ 20° Adjustment (Height)	Panel Type	Rapid IPS
Aspect Ratio 16:9 Brightness (nits) 300 (Typ.) Contrast Ratio 1200:1 DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE TECHNOLOGY AMD FreeSync™ HDR Ready 1 x DisplayPort (1.4) Video ports 1 x DisplayPort (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Fivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm <tr< th=""><th>Panel Resolution</th><th>2560 x 1440 (WQHD)</th></tr<>	Panel Resolution	2560 x 1440 (WQHD)
Brightness (nits) 300 (Typ.) Contrast Ratio 1200:1 DCR 1000000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE TECHNOLOGY AMD FreeSync™ HDR Ready 1 x DisplayPort (1.4) Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) 0.0 USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D	Pixel Pitch (H x V)	0.2331(H)x0.2331(V)
Contrast Ratio 1200:1 DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE TECHNOLOGY AMD FreeSync™ HDR Ready 1x DisplayPort (1.4) Video ports 1x DisplayPort (1.4) 2 x HDMI™ (2.0b) 2x HDMI™ (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm </th <th>Aspect Ratio</th> <th>16:9</th>	Aspect Ratio	16:9
DCR 100000000:1 Signal Frequency 64.56~266.4KHz(H) / 48~180Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (GtG) DYNAMIC REFRESH RATE TECHNOLOGY AMD FreeSync™ HDR Ready 1 x DisplayPort (1.4) Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) 0.0 USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design <t< th=""><th>Brightness (nits)</th><th>300 (Typ.)</th></t<>	Brightness (nits)	300 (Typ.)
Signal Frequency ACTIVATED RANGE Refresh Rate Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support HDR Ready Video ports USB ports N/A Audio ports 1 x Headphone out Viewing Angle Anti-glare Display Colors Power Type Power Input Adjustment (Tilt) Adjustment (Swivel) Adjustment (Height) Kensington Lock Dimension (W x D x H) Frameless Design I 804.56~266.4KHz(H) / 48~180Hz(V) 48~180Hz 64.56~266.4KHz(H) / 48~180Hz(V) 48~180Hz 64.56~266.4KHz(H) / 48~180Hz(V) 48~180Hz 64.56~266.4KHz(H) / 48~180Hz(V) 48~180Hz 40Hz	Contrast Ratio	1200:1
ACTIVATED RANGE Refresh Rate Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support HDR Ready Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) USB ports N/A Audio ports 1 x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Dimension (W x D x H) Frameless Design AMD FreeSync™ 1.49 2 x HDMI™ (2.0b) N/A 2 x HDMI™ (2.0b) AND FreeSync™ 1.49 2 x HDMI™ (2.0b) AMD FreeSync™ 1.49 2 x HDMI™ (2.0b) AMD FreeSync™ 1.49 2 x HDMI™ (2.0b) AMD FreeSync™ 1.49 2 x HDMI™ (2.0b) Author 2 x HDMI™ (2.0b) AMD FreeSync™ 1.49 2 x HDMI™ (2.0b) AMD FreeSync™ 1.40 2 x HDMI™ (2.0b) 1.40 2 x HDMI™ (2.0b) 1.41 2 x HDMI™ (2.0b) 1.42 2 x HDMI™ (2.0b) 1.41 1	DCR	100000000:1
Refresh Rate Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support HDR Ready Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Pimension (W x D x H) Frameless Design MDR Ready AMD FreeSync™ AMD FreeSync™ Imms (GtG) AMD FreeSync™ AMD FreeSync™ AMD FreeSync™ AMD FreeSync™ Imms (GtG) AMD FreeSync™ Imms (GtG) AMD FreeSync™ Imms (9.44) A D x Hone Ready A MD FreeSync™ Imms (9.44) A D x Hone Ready And I x D x Hone I x DisplayPort (1.4) 2 x HDMI™ (2.0b) AND I y 8° (V) Adobe Ready I x DisplayPort (1.4) 2 x HDMI™ (2.0b) I x DisplayPort (1.4) 2 x HDMI™ (2.0b) And I x D x Hone I x D x Ho	Signal Frequency	64.56~266.4KHz(H) / 48~180Hz(V)
Response time1ms (GtG)DYNAMIC REFRESH RATE TECHNOLOGYAMD FreeSync™HDR SupportHDR ReadyVideo ports1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)USB portsN/AAudio ports1x Headphone outViewing Angle178° (H) / 178° (V)Adobe RGB / DCI-P3 / sRGB90% / 94% / 125%Surface TreatmentAnti-glareDisplay Colors1.07B (8 bits + FRC)Power TypeExternal AdaptorPower Input100~240V, 50/60HzAdjustment (Tilt)-5° ~ 20°Adjustment (Swivel)-30° ~ 30°Adjustment (Pivot)-90° ~ 90°Adjustment (Height)0 ~ 130 mmKensington LockYesDimension (W x D x H)613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand)Carton Dimension (W X D X H)WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mmFrameless DesignYes	ACTIVATED RANGE	48~180Hz
DYNAMIC REFRESH RATE TECHNOLOGY HDR Support HDR Ready 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Carton Dimension (W x D x H) Frameless Design HDR Ready Al x Display Port (1.4) 2 x HDMI™ (2.0b) 1.4 x DisplayPort (1.4) 2 x HDMI™ (2.0b) 1.4 x DisplayPort (1.4) 2 x HDMI™ (2.0b) 1.4 x DisplayPort (1.4) 2 x HDMI 1.4 x DisplayPort (1.4) 2 x HDMI 1.4 x DisplayPort (1.4) 2 x HDMI 1.4 x DisplayP	Refresh Rate	180Hz
HDR Support HDR Ready Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) USB ports N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Height) Ves Carton Dimension (W x D x H) Frameless Design HDR Ready 1x Display Port (1.4) 2 x HDMI™ (2.0b) 1x DisplayPort (1.4) 2 x HDMI 1x DisplayPort (1.4) 2 x HON 1x DisplayPort (1.4) 2 x HOM 1x DisplayPort (1.4) 2 x H	Response time	1ms (GtG)
Video ports 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) N/A Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) Kensington Lock Yes Dimension (W x D x H) Carton Dimension (W X D X H) Frameless Design 1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) N/A Extending out 30° / 90° Anti-glare 100~240V, 50/60Hz -5° ~ 20° -30° ~ 30° -30° ~ 30° -310 mm (W x D x H) Surface Treatment -30° ~ 30° -3		AMD FreeSync™
2 x HDMI	HDR Support	HDR Ready
Audio ports 1x Headphone out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Video ports	
Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	USB ports	N/A
Adobe RGB / DCI-P3 / sRGB 90% / 94% / 125% Surface Treatment Anti-glare Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Audio ports	1x Headphone out
Surface TreatmentAnti-glareDisplay Colors1.07B (8 bits + FRC)Power TypeExternal AdaptorPower Input100~240V, 50/60HzAdjustment (Tilt)-5° ~ 20°Adjustment (Swivel)-30° ~ 30°Adjustment (Pivot)-90° ~ 90°Adjustment (Height)0 ~ 130 mmKensington LockYesDimension (W x D x H)613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand)Carton Dimension (W X D X H)WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mmFrameless DesignYes	Viewing Angle	178° (H) / 178° (V)
Display Colors 1.07B (8 bits + FRC) Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Adobe RGB / DCI-P3 / sRGB	90% / 94% / 125%
Power Type External Adaptor Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Surface Treatment	Anti-glare
Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) 613 x 61 x 369 mm (without Stand) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Display Colors	1.07B (8 bits + FRC)
Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Power Type	External Adaptor
Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Power Input	100~240V, 50/60Hz
Adjustment (Pivot) -90° ~ 90° Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Adjustment (Tilt)	-5° ~ 20°
Adjustment (Height) 0 ~ 130 mm Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (sithout Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Adjustment (Swivel)	-30° ~ 30°
Kensington Lock Yes Dimension (W x D x H) 613 x 228 x 539 mm (sithout Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm (outer: 858 x 165 x 500 mm) Frameless Design Yes	Adjustment (Pivot)	-90° ~ 90°
Dimension (W x D x H) 613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand) Carton Dimension (W X D X H) WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm Frameless Design Yes	Adjustment (Height)	0 ~ 130 mm
Carton Dimension (W X D X H) 613 x 61 x 369 mm (without Stand)	Kensington Lock	Yes
Frameless Design Outer:858 x 165 x 500 mm Yes	Dimension (W x D x H)	
	Carton Dimension (W X D X H)	
PIP / PBP Function N/A	Frameless Design	Yes
	PIP / PBP Function	N/A

FEATURES



Make sure the intensity and purity of colors when gaming.



180Hz High Refresh Rate

Experience smooth gaming with a blazing fast 180Hz refresh rate, that gives you the upperhand in fast moving games.



1ms Fast Response Time

ms Fast Response Time
GTG Eliminate screen tearing and choppy frame rates with 1ms response time.



Perfectly support 120Hz at FHD/WQHD resolution with next-gen console like PS5 and Xbox series X/S.



Adjustable Stand

Through adjustments of tilting, lowering and raising, and swiveling, easily change the position of the monitor for maximum ergonomics and optimum viewing experiences.



Wide Color Gamut

Wide Color Game colors and details will look more realistic and refined, to | Gamut push game immersion to its limits.





MSI gaming monitor is equipped with HDR technology that can produce images with more details, wider range of colors. Windows 11 Auto HDR supported



MONITORS G272QPF E2

ALL ABOUT GAMING

VESA Mounting	100 x 100 mm
Weight (NW / GW)	6.3 / 8.4kg
Note	Display Port: 2560 x 1440 (Up to 180Hz) HDMI 2.0b: 2560 x 1440 (Up to 144Hz) Adobe RGB, DCI-P3 and sRGB and Rec.2020 follow CIE1976 Standard

CONNECTIONS



- 1. 5-way joystick navigator
- 2. DC-in
- 3. 1 x Display Port (1.4)
- 4. 2 x HDMI[™] (2.0b)
- 5. Headphone out
- 6. Kensington lock